

Garage Door Controller

Product ref.: 150586A0



Product features

- Enables opening, closing and stopping of garage doors in connection with garage door drives
- Replaces conventional garage door controllers by an intelligently controlled solution
- Individual configuration and easy setup via Homematic WebUI
- Comfortable garage door control directly via the device itself, remote control or various apps of partners
- Particularly robust thanks to solid housing design
- Flexible application either with batteries, plug-in mains adapter or the garage door drive
- Easy mounting and installation with the supplied screws and plugs or using the cable bushings at the backside

Technical specifications

Supply voltage	2x 1.5 V LR6/Mignon/AA or 5-24 VDC
Current consumption	50 mA max.
Max. switching capacity	24 V, 1 A
Battery life	2 years (typ.)
Load type	ohmic load
Relay	NO contact
Cable type and cross section:	flexible cable without ferrule 0.08 to 1.5 mm ² , rigid cable 0.3 to 1.6 mm ²
Degree of protection	IP31
Ambient temperature	-10 to +55 °C
Dimensions (W x H x D)	85 x 85 x 30.5 mm
Weight	165 g (including batteries)
Radio frequency band	868.0-868.6 MHz 869.4-868.65 MHz
Typ. open area RF range	190 m



Exclusively for the Central Control Unit CCU2/CCU3. Operation via the Homematic IP Access Point available soon.

Logistical data

Product reference	150586A0
EAN code	4047976505869
Short description	HmlIP-WGC
Packing unit	60
Packing dimensions	122 x 112 x 73 mm
Weight incl. packaging	287.0 g

Package contents

Homematic IP Garage Door Controller
Mounting material (2x screws, 2x plugs)
1.5 V LR6/Mignon/AA batteries (2x)
User manual