

Wall-mount Remote Control – 6 buttons

Product ref.: 142308A0



Product features

- Wall-mount remote control for universal use with three individually configurable pairs of buttons for comfortable control of connected devices
- Can be used e.g. for switching lights on and off or for activating and deactivating the eco mode
- Individual labelling of buttons with replaceable labelling field
- Simple and flexible installation thanks to supplied adhesive strips or screws
- Easy to integrate into existing switches with 55 mm frames of the following manufacturers: Berker, Busch-Jaeger, GIRA, Merten, JUNG, Kopp and ELSO
- To enable operation, the device has to be connected with one of the following solutions:
 - Homematic IP Access Point with free smartphone app and free cloud service
 - Central Control Unit CCU2/CCU3 with local user interface WebUI
 - Third-party solutions of partners

Technical specifications

| | |
|-------------------------|--|
| Supply voltage | 2x 1.5 V LR03/Micro/AAA |
| Current consumption | 50 mA max. |
| Battery life | 4 years (typ.) |
| Degree of protection | IP20 |
| Ambient temperature | 5 to 35 °C |
| Dimensions (W x H x D) | without frame: 55 x 55 x 20 mm incl. frame: 86 x 86 x 22 mm |
| Weight | 95 g (including batteries) |
| Radio frequency band | 868.0-868.6 MHz 869.4-869.65 MHz |
| Typ. open area RF range | 200 m |

Logistical data

| | |
|------------------------|-------------------|
| Product reference | 142308A0 |
| EAN code | 4047976423088 |
| Short description | HmIP-WRC6 |
| Packing unit | 90 |
| Packing dimensions | 122 x 112 x 48 mm |
| Weight incl. packaging | 182.0 g |

Package contents

Homematic IP Wall-mount Remote Control – 6 buttons

Clip-on frame

Mounting plate

Double-sided adhesive strips (2x)

Screws 3.0 x 30 mm (2x) and plugs 5 mm (2x)

1.5 V LR03/Micro/AAA batteries (2x)

User manual